

6-in-1 Spray

Multipurpose penetrating, cleaning, and lubricating fluid

APPLICATIONS

Anti-seize/releasing oil, antioxidant, anti-corrosion, with good lubricating power.

Also cleans oil/grease/inorganic residues, removes bitumens.

For all kinds of rusted/seized mechanisms: hinges, pivots, rails, bolts, hardware...

Can be used as a cleaner for chains, bearings, slides...

Shake the aerosol before use – Spray from a 10-15 cm distance.

Keep away from heat, sparks, and flames. Do not expose to heat and temperatures exceeding 50°C. Even when empty, do not puncture or incinerate the container.

ADVANTAGES

High penetrating power.

Can be used upside-down for an easier manipulation of the spray.

Compatible with all plastics, elastomers, and paints.

Non-flammable propellant gas: CO₂.

TYPICAL CHARACTERISTICS

Properties	Units	Standards	6-in-1 Spray
Color	-	-	Colorless to yellow
Density at 15°C	kg/m ³	ISO 12185	800
Viscosity at 40°C	mm ² /s	ISO 3104	1.4
KB index	-	ASTM D 1133	97
Flash point (closed-cup)	°C	ISO 2719	62
Copper strip test	-	ISO 2160	1a
SRV Friction test	-	ASTM D 5707	0.09

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial advisor or downloaded at ms-sds.totalenergies.com